

### DAISY-7X1-W2-D

~50° wide beam with tighter cutoff. Variant with diffused lenses.

### **TECHNICAL SPECIFICATIONS:**

Dimensions	x mm
Height	0 mm
Fastening	pin, screw, clips
ROHS compliant	yes 🛈



#### **MATERIAL SPECIFICATIONS:**

Component	Type	Material	Colour	Finish
C17363_DAISY-7X1-W2-D	Linear lens	PMMA	milky	
C16872_DAISY-7X1-SHD	Shade	PC	black	gloss
C16876_DAISY-7X1-SHD-WHT	Shade	PC	white	gloss
C17051_DAISY-7X1-SHD-MATT	Shade	PC	black	matt
C17225_DAISY-7X1-SHD-WHT-MATT	Shade	PC	white	matt
C17533_DAISY-7X1-SHD-MET-MATT	Shade	PC	metal	matt
C18167_DAISY-7X1-SHD-MET	Shade	PC	metal	gloss

### **ORDERING INFORMATION:**

#### **Quantities for one set:**


Linear lens 1
Shade 1



# PRODUCT DATASHEET DAISY-7X1-W2-D

Component		Qty in box	MOQ	MPQ	Box weight (kg)
C17363_DAISY-7X1-W2-D  » Box size: 400 x 300 x 300 mm	Linear lens	312	192	24	7.0
C17051_DAISY-7X1-SHD-MATT  » Box size: 595 x 360 x 230 mm	Shade	156	192	24	6.7
C18167_DAISY-7X1-SHD-MET  » Box size: 595 x 360 x 230 mm	Shade	156	192	24	7.0
C17225_DAISY-7X1-SHD-WHT-MATT  » Box size: 595 x 360 x 230 mm	Shade	156	192	24	6.8
C16872_DAISY-7X1-SHD  » Box size: 595 x 360 x 230 mm	Shade	156	192	24	6.4
C16876_DAISY-7X1-SHD-WHT  » Box size: 595 x 360 x 230 mm	Shade	156	192	24	6.8
C17533_DAISY-7X1-SHD-MET-MATT  » Box size: 595 x 360 x 230 mm	Shade	156	192	24	6.5





See also our general installation guide: <a href="www.ledil.com/installation\_guide">www.ledil.com/installation\_guide</a>

3/14




### AUDAX III

LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm

FWHM / FWTM 59.0° / 94.0°
Efficiency 86 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:

C17533\_DAISY-7X1-SHD-MET-MATT






### AUDAX III

LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm

FWHM / FWTM 59.0° / 94.0°
Efficiency 88 %
Peak intensity 0.9 cd/lm
LEDs/each optic 4
Light colour White
Required components:

C18167\_DAISY-7X1-SHD-MET






# AUDAX III

LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm

FWHM / FWTM 60.0° / 95.0°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:

C17225\_DAISY-7X1-SHD-WHT-MATT






### AUDAX IIII

LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm

FWHM / FWTM 58.0° / 91.0°
Efficiency 75 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:

C17051\_DAISY-7X1-SHD-MATT








LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm

FWHM / FWTM 60.0° / 95.0°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:

C16876\_DAISY-7X1-SHD-WHT






## AUDAX III

LED LIGHT ENGINE DAISY 28 LEDs 277.5mm x 20mm

FWHM / FWTM 58.5° / 91.0°
Efficiency 76 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C16872\_DAISY-7X1-SHD




### **DESCRIPTION** LUMILEDS

LED LUXEON 2835 Line
FWHM / FWTM 59.0° / 94.0°
Efficiency 86 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4

LEDs/each optic 4
Light colour White
Required components:

C17533\_DAISY-7X1-SHD-MET-MATT






### **DESCRIPTION** LUMILEDS

LED LUXEON 2835 Line
FWHM / FWTM 59.0° / 94.0°
Efficiency 88 %

Peak intensity 0.9 cd/lm LEDs/each optic 4
Light colour White Required components:


C17532\_DAISY-7X1-SHD-MET






Published: 05/11/2019



























### **TRIDONIC**

LED LLE 24x280mm 750lm 8x0 LVD ADV1

FWHM / FWTM 60.0° / 92.0°
Efficiency 74 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour White
Required components:

C17051\_DAISY-7X1-SHD-MATT




### **TRIDONIC**

LED LLE 24x280mm 750lm 8x0 LVD ADV1

FWHM / FWTM 61.0° / 96.0°
Efficiency 88 %
Peak intensity 0.8 cd/lm
LEDs/each optic 4
Light colour White
Required components:


C16876\_DAISY-7X1-SHD-WHT



### **TRIDONIC**

LED LLE 24x280mm 750lm 8x0 LVD ADV1

FWHM / FWTM 60.0° / 92.0°
Efficiency 75 %
Peak intensity 0.7 cd/lm
LEDs/each optic 4
Light colour White
Required components:
C16872\_DAISY-7X1-SHD






### PHOTOMETRIC DATA (SIMULATED):

### CREE - LED

LED J Series 2835  $\mathsf{FWHM}\,/\,\mathsf{FWTM}$ 56.0° / 88.0° Efficiency 77 % Peak intensity 0.9 cd/lm

LEDs/each optic Light colour White

Required components: C16872\_DAISY-7X1-SHD




#### **OSRAM**

OSLON PURE 1010 (GW VJLPE1) LED

FWHM / FWTM 44.0° / 70.0° Efficiency 86 % Peak intensity 1.5 cd/lm LEDs/each optic 4 White Light colour

Required components:

C17225\_DAISY-7X1-SHD-WHT-MATT




### **SAMSUNG**

LED LM301Z Plus FWHM / FWTM 56.0° / 86.0° Efficiency 88 % Peak intensity 1 cd/lm LEDs/each optic 3

Light colour White Required components:

C18167\_DAISY-7X1-SHD-MET




## **SAMSUNG**

LM301Z Plus FWHM / FWTM 55.0° / 86.0° Efficiency 86 % Peak intensity 1 cd/lm LEDs/each optic 4

White Light colour Required components:

C17225\_DAISY-7X1-SHD-WHT-MATT



Published: 05/11/2019



### PHOTOMETRIC DATA (SIMULATED):

### **SAMSUNG**

LED LM301Z Plus


FWHM / FWTM 54.0° / 86.0° Efficiency 75 %

Peak intensity 0.9 cd/lm

LEDs/each optic 4

Light colour White Required components:

C17051\_DAISY-7X1-SHD-MATT



### SEOUL SEMICONDUCTOR

LED SEOUL DC 3030C

FWHM / FWTM 56.0° / 88.0°

Efficiency 78 %


Peak intensity 0.9 cd/lm

LEDs/each optic 4

Light colour White

Required components:

C16872\_DAISY-7X1-SHD



### **TRIDONIC**

LED LLE 24x280mm 750lm 8x0 LVD ADV1


FWHM / FWTM 56.0° / 88.0°

Efficiency 88 %
Peak intensity 1 cd/lm

LEDs/each optic 4
Light colour White

Required components:

C17533\_DAISY-7X1-SHD-MET-MATT



Published: 05/11/2019



#### **GENERAL INFORMATION:**

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### **MATERIALS:**

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### **LEDIL Oy**

Joensuunkatu 13 FI-24240 SALO Finland

#### LEDiL Inc.

228 West Page Street Suite D Sycamore IL 60178 USA

# Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405, Block B Casic Motor Building Shenzhen 518057 P.R.CHINA

# Local sales and technical support

www.ledil.com/ where\_to\_buy

#### **Shipping locations**

Salo, Finland Hong Kong, China

#### **Distribution Partners**

14/14

www.ledil.com/ where\_to\_buy