



Data
Technical data

Main product function	Operating tool
Number of pitches	1 -way

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Physical data

Depth	50 mm / 1.97 inch
Pin spacing	3.5/3.81 mm

Mechanical data

Suitable	for 734, 2734 Series
----------	----------------------

Material data

Color	black
Insulation material	Glass fiber-reinforced polyamide (PA66 GF)
Fire load	0.036 MJ
Weight	1.2 g

Commercial data

Product Group	3 (Multi Conn. System)
PU (SPU)	100 (25) Stück
Packaging type	box
Country of origin	DE
GTIN	4045454272173
Customs tariff number	82055980000

Approvals / Certificates

Ship Approvals

Logo	Approval	Additional Approval Text	Certificate name
	LR Lloyds Register	IEC 61984	96/20035 (E5)

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 734-231	URL	Download
Operating tool; black		

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.

Installation Notes



Conductor termination parallel to CAGE
CLAMP® actuation



Inserting a conductor via operating lever.

Subject to changes. Please also observe the further product documentation!