

## **TECHNICAL** DATASHEET

## PRODUCT

# Moisture Barrier Bag 3.6MIL

#### CONSTRUCTION

Seal

The 3.6MIL bag features an antistatic metallized polyester outer layer and an antistatic inner layer. In between are layers of static dissipative polyethylene, nylon and an aluminium foil shield.



#### Bag Opening

#### FEATURES

- Protects electronics from moisture and static damage
- Opaque and light tight to offer additional protection
- Firm lamination and heat sealing offers superior resistance to vapour and oxygen
- Surface resistance of 10<sup>8</sup>-10<sup>11</sup> Ohms
- These bags are ideal for transporting and storing sensitive devices such as circuit boards and electronic components.
- Available in 3.6 / 4.4 and 6Mil thicknesses
- Flexible structure & easy to vacuum seal

#### CONFIGURATION(S)

Our bags are available in custom sizes or in several industry standard sizes. Bags are offered in a 3-seal configuration, with our standard flexographically printed artwork. Our bags can also be personalized with your company logo on bespoke orders. Minimum order quantities apply.

To request a quotation or for more information, please call **+1 512-580-4220** email <u>sales@antistat.com</u> or visit **www.antistat.com** 



## **TECHNICAL** DATASHEET



LEVEL	FLOOR LIFE (OUT OF THE BAG) AT FACTORY AMBIENT 30°C / 60% RH OR AS STATED
1	Unlimited at 30°C / 85% RH
2	1 Year
2a	4 Weeks
3	168 Hours
4	72 Hours
5	48 Hours
5a	24 Hours
6	Mandatory bake before use. After bake must be reflowed within the time amit specified on the Jabel.

#### BAG ARTWORK

Our moisture barrier bags are produced with the following sample artwork as standard. For further information on bespoke/printed orders, please contact one of our sales team. Please note there is a minimum order quantity of 20,000 bags on all custom printed bags.

Note: All of our custom moisture barrier bags are batch coded for QC traceability.

MOISTURE BARRIER BAG
ANT018MBB
THIS BAG IS RoHS COMPLIANT
CONFORMS TO PC/JEDEC J-STD-033

ATTENTION THIS BAG CONTAINS MOISTURE & ELECTROSTATIC SENSITIVE DEVICES





To request a quotation or for more information, please call **+1 512-580-4220** email <u>sales@antistat.com</u> or visit **www.antistat.com** 



#### **TEST CONDITIONS**

The following results were taken under the following environmental test conditions: Temperature:  $23^{\circ}C$  / Humidity: 12%

ITEM	TEST METHOD	TYPICAL VALUE	
Film Composition	N/A	PET/AL/NY/PE	
Inner and Outer Resistance	STM.11.11	10 <sup>8</sup> - 10 <sup>11</sup> Ohms	
Moisture Vapour Transmission Rate (100F, 100in 2/24 hrs)	ASTM F 1249	<=0.035 gram/100sq/in / 24 hours	
Tensile Strength	ASTM D882	7500 PSI	
Puncture Resistance	ASTM F1306-90(2002)	24lbs	
Heat Seal Temperature	-	300-410°F	
Heat Seal Time	-	0.5-3.5 sec	
Heat Seal Pressure	-	30-70 PSI	
Seal Strength	GB/96-04-10	12lbs	
Static Decay Time	IEC61340-5-1 (±1000 - ±100V)	≤2S	

#### **TEST CONDITIONS**

The anti-static moisture barrier bag is tested accordant with the relevant test standard and requirements.

Test Item:	Test Method:	Measured Equipment(s):	MDL:
Lead (Pb)	IEC 62321:2008 Ed.1 Sec.8	ICP-OES	2mg/kg
Cadmium (Cd)	IEC 62321:2008 Ed.1 Sec.8	ICP-OES	2mg/kg
Mercury (Hg)	IEC 62321:2008 Ed.1 Sec.7	ICP-OES	2mg/kg
Hexavalent Chromium (Cr(VI))	IEC 62321:2008 Ed.1 Annex C	UV-Vis	2mg/kg
Polybrominated Biphenyls (PBBs)	IEC 62321:2008 Ed.1 Annex A	GC-MS	5mg/kg
Polybrominated Diphenyl Ethers (PBDEs)	IEC 62321:2008 Ed.1 Annex A	GC-MS	5mg/kg

EMI Shielding: Meets required range of EN 61340-5-1 tested per IEC 61340-2-3 and ANSI/ESD STM11.31

To request a quotation or for more information, please call +1 512-580-4220 email <u>sales@antistat.com</u> or visit www.antistat.com



PRODUCT CODE	DESCRIPTION	SIZE (inch)	SIZE (mm):	NOTES
018-0001	Moisture Barrier Bag 3.6Mil / 92 microns	6 x 28	152.4 x 711.2	Pack of 100
018-0400	Moisture Barrier Bag 3.6Mil / 92 microns	10 x 20	254 x 508	Pack of 100
018-0401	Moisture Barrier Bag 3.6Mil / 92 microns	10 x 24	254 x 610	Pack of 100
018-0301	Moisture Barrier Bag 3.6Mil / 92 microns	10 x 26	254 x 660.4	Pack of 100
018-0402	Moisture Barrier Bag 3.6Mil / 92 microns	12 x 20	304.8 x 508	Pack of 100
018-0007	Moisture Barrier Bag 3.6Mil / 92 microns	16 x 18	406 x 457	Pack of 100
018-0403	Moisture Barrier Bag 3.6Mil / 92 microns	18 x 18	457 x 457	Pack of 100
018-0300	Moisture Barrier Bag 3.6Mil / 92 microns	22 x 24	558.8 x 609.6	Pack of 100
018-0130	Moisture Barrier Bag 3.6Mil / 92 microns	4 x 6	101.6 x 152.4	Pack of 100
018-0131	Moisture Barrier Bag 3.6Mil / 92 microns	6 x 12	152.4 x 304.8	Pack of 100
018-0134	Moisture Barrier Bag 3.6Mil / 92 microns	6 x 26	152.4 x 660.4	Pack of 100
018-0136	Moisture Barrier Bag 3.6Mil / 92 microns	8 x 10	203.2 x 254	Pack of 100
018-0410	Moisture Barrier Bag 3.6Mil / 92 microns	8 x 20	203.2 x 508	Pack of 100
018-0137	Moisture Barrier Bag 3.6Mil / 92 microns	12 x 16	304.8 x 406	Pack of 100
018-0304	Moisture Barrier Bag 3.6Mil / 92 microns	23 x 32	584.2 x 812.8	Pack of 100
018-0038	Moisture Barrier Bag 3.6Mil / 92 microns	26 x 19	680 x 400	Pack of 50
018-0015	Moisture Barrier Bag 3.6Mil / 92 microns	29 x 23	750 x 600	Pack of 50

Note: Other sizes and thicknesses available upon request.

To request a quotation or for more information, please call **+1 512-580-4220** email <u>sales@antistat.com</u> or visit **www.antistat.com**