

Sep. 1. 2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	
△					△					
△					△					
APPLICABLE STANDARD										
RATING	OPERATING TEMPERATURE RANGE	- 3 5 °C TO 8 5 °C(NOTE1)			STORAGE TEMPERATURE RANGE	- 1 0 °C TO 6 0 °C				
	VOLTAGE	5 0 V A C			APPLICABLE CONNECTOR	DF23A/C-18DS-0.5V				
	CURRENT	0. 3 A								
SPECIFICATIONS										
ITEM	TEST METHOD				REQUIREMENTS				QT	AT
CONSTRUCTION										
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				x	x
MARKING	CONFIRMED VISUALLY.								x	x
ELECTRICAL CHARACTERISTICS										
CONTACT RESISTANCE	100 mA (DC OR 1000 Hz).				60 mΩ MAX.				x	—
INSULATION RESISTANCE	100 V DC.				500 MΩ MIN.				x	—
VOLTAGE PROOF	150 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				x	—
MECHANICAL CHARACTERISTICS										
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.				INSERTION FORCE: 28 N MAX. EXTRACTION FORCE: 2.7 N MIN.				x	—
MECHANICAL OPERATION	50 TIMES INSERTIONS AND EXTRACTIONS.				① CONTACT RESISTANCE: 60 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				x	—
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				x	—
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				① NO ELECTRICAL DISCONTINUITY OF 1 μs. ② NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				x	—
ENVIRONMENTAL CHARACTERISTICS										
DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.				① CONTACT RESISTANCE: 60 mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				x	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE: -55→ 5 TO 35→85→ 5 TO 35 °C TIME: 30→10 TO 15→30→10 TO 15 min UNDER 5 CYCLES.				① CONTACT RESISTANCE: 60 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK AND LOOSENESS, OF PARTS.				x	—
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.				① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.				x	—
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JEIDA-39)				① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.				x	—
REMARKS					DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
NOTE1: INCLUDE THE TEMPERATURE RISING BY CURRENT.					T. Yamamoto '03. 10. 1	<i>T. Yamamoto</i> '03. 10. 2	<i>K. Akijama</i> '03. 10. 2	<i>K. Akijama</i> '03. 10. 2		
Unless otherwise specified, refer to IEC60512										
Note QT: Qualification Test AT: Assurance Test x: Applicable Test										
HRS HIROSE ELECTRIC CO., LTD.					SPECIFICATION SHEET			PART NO. DF23C-18DP-0.5V(92)		
CODE NO. (OLD) CL			DRAWING NO. ELC4-164161-04			CODE NO. CL688-0808-7-92			1 1	

TO