




Figure similar

SIPLUS LOGO! 12/24RCE -20 ... +70°C start up -20°C with conformal coating based on 6ED1052-1MD08-0BA0 . Logikmodul, Display SV/E/A: 24V/24V/24V trans., 8DE (4AE)/4DA, SP. 400 blocks, modular erweiterbar, Ethernet integr. Web-Server, Datalog, benutzerdefinierte Web-Seiten, Standard microSD-Karte für LOGO! Soft Comfort ab V8, ältere Projekte ablauffähig

| Display | |
|---|---|
| with display | Yes; The legibility and response time of the display may be reduced or lengthened at temperatures outside 0 ... +55 °C. These effects are self-reversing on return to the normal temperature range of 0 ... +55 °C. |
| Installation type/mounting | |
| Mounting | on 35 mm DIN rail, 4 spacing units wide |
| Supply voltage | |
| permissible range, lower limit (DC) | 10.8 V |
| permissible range, upper limit (DC) | 28.8 V |
| Time of day | |
| Time switching clocks | |
| • Number | 400; Max. 400, function-specific |
| • Power reserve | 480 h |
| Digital inputs | |
| Number of digital inputs | 8; Of which 4 can be used in analog mode (0 to 10 V) |
| Digital outputs | |
| Number of digital outputs | 4; Relays |
| Short-circuit protection | No; external fusing necessary |
| Output current | |
| • for signal "1" permissible range for 0 to 55 °C, max. | 10 A |
| Relay outputs | |
| Switching capacity of contacts | |
| — with inductive load, max. | 3 A |
| — with resistive load, max. | 10 A |
| EMC | |
| Emission of radio interference acc. to EN 55 011 | |
| • Limit class B, for use in residential areas | Yes |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | -25 °C; = Tmin; Startup @ -20 °C |
| • max. | 70 °C; Tmax; Tmax > +55 °C max. load 1 A per relay or max. load 3 A per relay and half the number of DIs (no adjacent points) |
| • At cold restart, min. | -20 °C; incl. condensation / frost permitted (no commissioning under condensation conditions) |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |

| | |
|---|--|
| Altitude during operation relating to sea level | |
| <ul style="list-style-type: none"> • Installation altitude above sea level, max. • Ambient air temperature-barometric pressure-altitude | 5 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| <ul style="list-style-type: none"> • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation |
| Resistance | |
| Coolants and lubricants | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| Conformal coating | |
| <ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 • Protection against fouling acc. to EN 60664-3 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Class 2 for high reliability Yes; Type 1 protection Yes; Discoloration of coating possible during service life Yes; Conformal coating, Class A |
| Dimensions | |
| Width | 71.5 mm |
| Height | 90 mm |
| Depth | 60 mm |
| last modified: | 12/18/2020  |