

Features

- High Density Cell Design for Extremely Low $R_{DS(ON)}$
- Rugged and Reliable
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings



- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Maximum Thermal Resistance: 100°C/W Junction to Ambient^(Note1)

Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	20	V
Gate-Source Voltage	V_{GS}	± 8	V
Continuous Drain Current	I_D	3	A
Pulsed Drain Current ^(Note2)	I_{DM}	10	A
Total Power Dissipation	P_D	1.25	W

Note 1. Surface Mounted on FR4 Board, $t < 10$ sec.


2. Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature.

Internal Structure and Marking Code



Dual N-Channel Mosfet

SOT23-6L



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.012	0.020	0.30	0.50	
B	0.051	0.070	1.30	1.80	
C	0.087	0.126	2.20	3.20	
D	0.037		0.95		TYP.
G	0.074		1.90		TYP.
H	0.106	0.122	2.70	3.10	
J	0.002	0.006	0.05	0.15	
K	0.030	0.051	0.75	1.30	
L	0.012	0.024	0.30	0.60	
M	0.003	0.008	0.08	0.22	

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Off Characteristics						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =10μA	20			V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =20V, V _{GS} =0V			1	μA
Gate-Source Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±8V			±100	nA
On Characteristics ^(Note 3)						
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =50μA	0.55		1.25	V
Drain-Source On-Resistance	R _{DS(on)}	V _{GS} =4.5V, I _D =3.6A		20	30	mΩ
		V _{GS} =2.5V, I _D =3.1A		30	40	
Forward Tranconductance	g _{FS}	V _{DS} =5V, I _D =3.6A		8.5		S
Dynamic Characteristics ^(Note 4)						
Input Capacitance	C _{iss}	V _{DS} =10V,V _{GS} =0V,f =1MHz		500		pF
Output Capacitance	C _{oss}			100		
Reverse Transfer Capacitance	C _{rss}			60		
Switching Characteristics ^(Note 4)						
Turn-On Delay Time	t _{d(on)}	V _{GS} =4.5V,V _{DD} =10V,I _D =3.6A, R _{GEN} =6Ω		23	45	ns
Turn-On Rise Time	t _r			11	30	
Turn-Off Delay Time	t _{d(off)}			34	70	
Turn-Off Fall Time	t _f			36	70	
Total Gate Charge	Q _g	V _{DS} =10V, I _D =3.6A,V _{GS} =4.5V		6	10	nC
Gate-Source Charge	Q _{gs}			1.4		
Gate-Drain Charge	Q _{gd}			1.8		
Drain-Source Diode Characteristics and Maximum Ratings						
Drain-Source Diode Forward Current	I _S				3	A
Diode Forward Voltage ^(Note 3)	V _{SD}	V _{GS} =0V, I _S =3A			1.2	V

Note: 3. Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

4. Guaranteed by Design, Not Subject to Production Testing.

Curve Characteristics

Fig. 1 - Typical Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - Capacitance Characteristics




Fig. 4 - Normalized On-Resistance




Fig. 5 - Threshold Voltage Characteristics





Fig. 6 - Total Gate Charge Characteristics



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

Note : Adding "-HF" Suffix for Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.