



Temperature Controller

RE 56



Measure



Control



Record



Analyze

Temperature Controller

RE 56



The controller is designed for the temperature control. Controller works directly with the resistance sensors or thermocouple sensors. The controller is equipped with outputs that allows for control and alert signalization. Control output can be programmed for PID or ON/OFF algorithm.

Applications:

- Plastics Industries
- Food Industries
- Dehydration Industries

Product Features:

Programmable input temperature sensors:

- ▶ RTD : PT100(2 or 3 wire)
- ▶ Thermocouple: J,T,K,S,R

Independent Relay output & SSR output:

- ▶ Either Relay or SSR output can be configured to Control output while other output can be used as Alarm Output

Control Output:

- ▶ Control Method : ON-OFF ,PID.
- ▶ Type of control output : Relay or SSR

Alarm Output:

- ▶ Different Alarm modes available.
- ▶ Type of alarm output : Relay or SSR.

Configuration through:

- ▶ Front keys.

Auto Tunning Function

- ▶ Auto tuning of PID Parameters.

Measurement are available on:

- ▶ 3 digit 7 segment display with 14.2 mm digit height

Manual mode

- ▶ Output can be controlled manually.

Timer Function

- ▶ Control Output can be configured for timer function. Timer output can be assigned to following functions
 - 1.Stop Control Output
 - 2.Switch to Manual Mode
 - 3.Start Auto Tunning
 - 4.Stop Auto tuning
- ▶ Alarm Output can be configured to Timer Alarm

Output on Sensor Failure

- ▶ User can set the value for safe operation of process on failure of input sensor

Input Digital filter

- ▶ The time constant of the filter can be set from 0 to 99.9 sec.

Heating / Cooling control

- ▶ Output can be configured as Heating or Cooling control.

Enclosure Protection for dust and water:

- ▶ Conforms to IP 54 for front face as per IEC 60529.

Compliance to International Safety standards

- ▶ Compliance to International Safety standard IEC 61010-1- 2010.



Measure



Control



Record






Analyze

Datasheet subject to change without notice

Temperature Controller

RE 56

Dimensions Details :



Technical Specifications:

Input Signals:

Input type	Ranges	
Pt100	-199 ... 850°C	-199 ... 999°F
Fe-CuNi (J)	-100 ... 999°C	-148 ... 999°F
Cu-CuNi (T)	-100 ... 400°C	-148 ... 752°F
NiCr-NiAl (K)	-100 ... 999°C	-148 ... 999°F
PtRh10-Pt (S)	0 ... 999°C	32 ... 999°F
PtRh13-Pt (R)	0 ... 999°C	32 ... 999°F

Measurement time: 0.2 sec

Resolution 1 °

Auxiliary Supply:

Higher Aux	60 V – 280 V AC/DC
Higher Aux supply frequency	45 to 65 Hz range
Higher Aux Nominal Value	230 V AC/DC 50/60 Hz for AC Aux

VA Burden:

Auxiliary Supply burden < 6VA approx.

Types of outputs:

Relay contact	SPDT-NO/NC, rated load: 10A,250VAC / 30VDC
SSR drive output	12VDC, maximum load capacity: 40 mA

Accuracy :

Reference Conditions	23°C
RTD	0.1% of range ± 1°C
Thermocouple	0.25% of range (0.5% of range - for R,S) ± 1°C

Influence of Variations

Temperature coefficient 0.025% / Deg

Applicable Standards:

EMC immunity	IEC 61326 - 1 : 2012, Table 2 *
Safety	IEC 61010-1-2010 , Permanently connected use
IP for water & dust	IEC60529
Pollution degree:	2
Installation category:	II

*Note:- The instrument continues to operate at a measuring accuracy of within ± 2% of the range during test.



Measure




Control



Record



Analyze



RISHABH



Measure



Control



Record



Analyze

RISHABH INSTRUMENTS PVT. LTD.

Domestic (India): +91 253 2202028/99 | marketing@rishabh.co.in

International: +91 253 2202004/06/08/99 | global@rishabh.co.in

www.rishabh.co.in