



MATERIALS AND FINISH:

SLIDE LOCK BAR:	STAINLESS STEEL
MOUNTING SCREW:	STEEL, NICKEL PLATED
FLAT WASHER:	STEEL, NICKEL PLATED
LOCK WASHER:	STEEL, NICKEL PLATED
4-40 NUT:	STEEL, NICKEL PLATED

KIT INCLUDES:

- (1X) SLIDE LOCK BAR
- (2X) #4-40 MOUNTING SCREW
- (2X) FLAT WASHERS
- (2X) LOCK WASHERS
- (2X) #4-40 NUTS

DIMENSIONS(inch)	
ITEM NO.	THICKNESS
2	0.020 REF
3	0.031 REF
4	0.074 REF

For back shell assembly applications:
ONLY use the mounting screws when mounting slide lock bar
DO NOT use the flat washers, lock washers, and #4-40 nuts

RoHS COMPLIANT



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:
W. ROBBINS

DATE:
12/05/2005

UNITS = inch [mm]

DO NOT SCALE FROM DRAWING

NorComp

SCALE: NTS	SHEET 1	OF 1	REV 7
DWG NO. 160-015-003R031			