



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Compact 1-Port USB-C Wall Charger - GaN Technology, 20W PD3.0 Charging, White

MODEL NUMBER: U280-W01-20C1-G



Travel-sized USB-C charger provides up to 20W to quickly and efficiently charge your smartphone or laptop at home or on the move.

Features

20W USB Type-C Charger Gets Your Mobile Device Ready in a Hurry, Wherever You Are

This single-port USB charger lets you quickly and safely charge your USB-C mobile device. Plug it into any NEMA 1-15R, NEMA 5-15R or NEMA 5-15/20R AC outlet to ensure your laptop, smartphone, tablet or other USB-C device charges at its fastest possible speed. The USB-C port supports USB Power Delivery (PD) 3.0 charging up to 5V 3A (15W) and 9V 2.22A (20W).

Gallium Nitride Technology Allows High-Wattage Capacity in a Compact Package

This USB wall charger is smaller and lighter than most standard wall chargers that come with a laptop, measuring less than 2.5 cubic inches. Ideal for travel, it is designed using GaN technology, which has a higher power density than silicon and provides higher efficiency than standard USB-C fast chargers. It also operates under much cooler temperatures, despite its small size, meaning it won't get hot while charging your device.

Built-In Auto-Sensing Adjusts to Proper Power Level to Get Your Device to 100%

The USB-C port features auto-sensing technology that automatically adjusts to your device's appropriate power level, perfect for fast-charging tablets and e-readers. The unit protects against overheating, overcurrent, overcharging and short circuits. In fact, it stops charging as soon as your device's batteries are at full capacity.

Folding Plug Design Perfectly Sized for Travel

The compact USB Type-C charger, small enough to fit in the palm of your hand, is easy to carry in your purse, suitcase, backpack or laptop bag. The NEMA 1-15P plug folds into the unit when not in use to shield it from damage and prevent it from snagging or scratching your bag's contents.

Highlights

- Ideal for charging smartphones, tablets, e-readers and laptops while traveling
- USB-C PD 3.0 port supports a maximum power capacity of 20W for fast charging
- Gallium nitride (GaN) technology generates less heat to support high-efficiency charging
- Connects to any NEMA 1-15R, 5-15R or 5-15/20R AC outlet for immediate charging
- Measures less than 2.5 cu. in., making it perfectly sized for convenient travel use

Applications

Charge a smartphone, tablet, laptop or other USB-C mobile device without taking up a valuable USB port on your computer

Package Includes

U280-W01-20C1-G USB-C Wall Charger with PD Charging

Specifications

OVERVIEW

UPC Code

037332259899



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Product Type	Wall Charger
Charging Form Factor	Direct Plug-In
Device Compatibility	Computer
Technology	USB
INPUT	
Nominal Input Voltage(s) Supported	120V AC; 230V AC
Input Connection Type	NEMA 1-15P
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240
Input Frequency	50/60 Hz
Input Plug Type	NEMA 1-15P (NON-POLARIZED)
Input Current	100-240V, 1.0A (Max)
OUTPUT	
Output Capacity	5V 3A (15W), 9V 2.22A (20W)
Overload Protection	Yes
POWER	
Power Consumption (Watts)	20
USB Power Delivery (PD) Charging Support	Yes
USB Power Delivery (PD) Charging Specification	3.0
USER INTERFACE, ALERTS & CONTROLS	
LED Indicators	Blue - Power
CHARGING	
Number of Charging Ports	1
Total Charging Amps	3A
Total Charging Watts	20
Charging Method	USB
Charging Port Type	USB C (FEMALE)
Charging Ports Details	5V/3A (15W), 9V/2.22A (20W)
Charging Ports / Amps	(1) 3A
Compatible Devices	Smartphone; Tablet
Charging Method Detail	Power Delivery 3.0
PHYSICAL	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Material of Construction	PC (Plastic)
Color	White
Unit Dimensions (hwd / in.)	1.09 x 1.56 x 1.36
Unit Dimensions (hwd / cm)	2.77 x 3.95 x 3.45
Unit Packaging Type	Box
Unit Weight (lbs.)	0.09
Unit Weight (kg)	0.04
ENVIRONMENTAL	
Operating Temperature Range	0 to 77 °F (0 to 25 °C)
Storage Temperature Range	-4 to 185 °F (-20 to 85 °C)
Operating Humidity Range	20 to 90% RH, Non-Condensing
Storage Humidity Range	5 to 95% RH, Non-Condensing
Power Provided to Connected Device(s)	USB-C: 5V/3A (15W), 9V/2.22A (20W)
CONNECTIONS	
Number of Ports	1
Side A - Connector 1	NEMA 1-15P (NON-POLARIZED)
Side B - Connector 1	USB C (FEMALE)
FEATURES & SPECIFICATIONS	
Over Current Protection	Yes
Driver Required	No
Quick Charge Compliant	No
Overcurrent Protection	Yes
Overvoltage Protection	Yes
GaN Technology	Yes
STANDARDS & COMPLIANCE	
Product Certifications	NOM (Mexico); UL Listed
Product Compliance	RoHS; REACH; WEEE; FCC (USA)
WARRANTY	
Product Warranty Period (Worldwide)	2-year limited warranty



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>