VUE-2101 Series 10.1" Panel Mount Monitor



Features


- 10.1" active screen size
- 6-axis color adjustment (Green/Red/Blue/Cyan/Magenta/Yellow) for high level and more accuracy customized image
- Full-flat cover glass for extremely simple and elegant surface design
- Anti-glare (AG) treatment on screen for comfortable viewing experience
- Built-in multiple I/O interfaces for diverse media connectivity
- Adopts industrial-grade components for guaranteed performance
- Mount with multi-way and easy to extend peripheral devices (box PC/camera...)
- Front IP65 water-proof rating and IK08 high-level impact protection

(for PCAP touch model)

- Support 10-point touch function (PCAP technology)
- Excellent noise immunity well-suited for rugged applications (CS 10V)
- Support many touch method including fingers, glove, and stylus

Specifications

Model			PCAP touch	None touch
Brand			Advantech	
Display	Active Screen Size		10.1 inch	
	Resolution		1280 x 800 (WXGA)	
	Brightness		500 nits	
	Contrast Ratio		1000:1 (Typ.)	
	Aspect Ratio		16:10	
	Viewing Angle		85° / 85° / 85° / 85°	
	Response Time		25 ms (Typ.)	
	Backlight Life (hours)		50,000 (Typ.)	
Touch	Touch Type		Projected Capacitive Touch (PCAP)	N/A
	Touch Function		10 points	N/A
	Touch Interface		USB	N/A
		Video	VGA x 1, HDMI x 1, DVI-D x 1, DisplayPort x 1	
	Input	Audio	Audio line in x 1	
	IIIput	Control	USB typeB x 1 (for touch function)	
Connectivity		Others	USB3.0 x 2	
	Output	Video	N/A	
		Audio	2W+2W Internal Speaker	
		Control	N/A	
Control	OSD Function		Hot key (ON/OFF, LIFT, RIGHT, MENU, AUTO)	
	OSD Language		English, French, Korea, Portuguese, Russian, Simplified Chinese, Spanish, Traditional Chinese	
	Power Type		DC input, 19V Adaptor	
Power	Power Input		100-240V _{AC} , 50-60Hz, 1.5A	
	Power Consumption		15W	
	Operating	Temperature	0°C-+40°C	
Environment		Humidity	10% to 85% (non-condensing)	
Environment	Storage	Temperature	-20°C-+60°C	
	- J	Humidity	5% to 80% (non-condensing)	
	Housing Material		0.8 mm sheet metal (Black)	
	VESA Compatibility		100 x 100 mm	
Mechanical Specification	Dimensions (W x H x D)	Physical	257.93 x 179.33 x 50.22 mm	
		Packing	333 x 195 x 245 mm	
	Weight	Net	1.5 Kg	
		Gross	3.0 Kg	
Installation	Mounting on a wall/machine		100 x 100 mm, VESA grid	
	Mounting with stand/arm		100 x 100 mm, VESA grid	
	Mounting through bracket		64 mm, Side mount screw hole	
Approbation	Certificates		CB, UL, BSMI, CCC, CE, UKCA, FCC, CEC, ErP lot5	
Warranty			2-year (1-year for panel)	



Ordering Information

Part Number		Description	Decking Link	
PCAP touch model	None touch model		Packing List	
VUE-2101-WX50PA-A4	VUE-2101-WX50MA-A4	Advantech 10.1" WXGA Panel Mount Monitor (incl. Japan, Korea, Australia, and Middle East Power Cord)	 Power Cord (1.5M, Black) Power Adaptor (1.5M, Black) VGA Cable (1.5M, Black) 	
VUE-2101-WX50PC-A4	VUE-2101-WX50MC-A4	Advantech 10.1" WXGA Panel Mount Monitor (incl. China Power Cord)	 HDMI Cable (1.5M, Black) DisplayPort Cable (1.5M, Black) DVI Cable (1.5M, Black) USB Cable (1.8M, Black), for touch, PCAP 	
VUE-2101-WX50PX-A4	VUE-2101-WX50MX-A4	Advantech 10.1" WXGA Panel Mount Monitor (incl. Europe, Taiwan, UK and US Power Cord)	model only Audio Cable (1.5M, Black) Side Mount Bracket kit Startup Manual (Paper)	

Optional Accessories

Part Number	Description
960T-A15DEE-B0	Active Stylus Pen for VUE-2000 series, Black
960T-SD-10H10-L	Desktop Stand for VUE-2000, VESA100x100, Large, support up to 7kg
960T-BT-V2K101	VUE-2101 Bracket kit