

SPEED2 LE Express 2 Port PCIe Serial Card

 perle.com/products/pci-express-serial-port-cards/speed2le-express-dual-port-serial-card.shtml

RS232 Serial Cards

- 2 on-board DB9M RS232 ports
- PCI Express (PCIe) bus slot support
- Low profile card with standard bracket and low profile bracket included
- 16550 UART for software compatibility
- 921.6Kbps bi-directional serial communication speeds
- 15 kV electrostatic discharge protection
- Full modem control and hardware/software flow control

Availability: **in stock**

Part Number: 04003310



[Buy Now](#) [Volume Pricing](#)

Supported Operating System Drivers

- Windows® Server 2016
- Windows® 10
- Windows® Server 2012 R2
- Windows® 8.1 (32 / 64 Bit)
- Windows® Server 2012
- Windows® 8 (32 / 64 Bit)
- Windows® Server 2008 R2
- Windows® 7 (32 / 64 Bit)
- Windows® Server 2008 (32 / 64 Bit)
- Windows® Vista (32 / 64 Bit)
- Windows® Server 2003 (32 / 64 Bit)
- Windows® XP (32 / 64 Bit)
- Windows® 2000
- Linux 3.x, 2.6.x, 2.4.x, 2.2.16+ (32 / 64 Bit)

For Solaris x86, Solaris SPARC, SCO OpenServer and SCO UnixWare, we recommend [UltraPort Express Serial Cards](#).

Connectors

- 2x DB9
- [EIA 232 Pinout](#)

Serial Port Protection

15Kv Electrostatic Discharge Protection (ESD)

Signal support

TXD, RXD, RTS, CTS, DTR, DCD, DSR, RI

UART

16C950 (16C550 compatible)

Environmental

Reach, RoHS and WEEE Compliant

Approvals



- FCC Part15 ,Class B
- EN55022:1998 + A1:2000 + A2:2003 Class A
- EN55024:1998 + A1:2001 + A2:2003
- EN60950-1:2001 +A11:2004

Form Factor

Speed 2 LE Express are low profile MD1 cards shipped on standard sized brackets. Low profile brackets are included

X1 lane - inserts into x1, x4, x8 and x16 lane PCI Express (PCIe) slots

Warranty: Limited Lifetime Warranty

HSTUS Number: 8517.62.0050

ECCN Number: 5A991

Copyright © 1996 - 2021 Perle. All Rights Reserved