



**Product:** <u>9989</u> ☑

Lead Wire, #14 Str TC, PVC Ins, AWM 1569

# Request Sample

# **Product Description**

Low Temp Plastic Lead Wire, 14AWG (41x30) Tinned Copper, PVC Insulation, AWM 1569 CSA TYPE TR-64 AND TRSR-64

## **Technical Specifications**

## **Product Overview**

Suitable Applications: inter-connection circuits, internal wiring of computer and electronic equipments, internal wiring of appliances

## **Physical Characteristics (Overall)**

#### Conductor

AWG	Stranding	Material	No. of Conductors
14	41x30	TC - Tinned Coppe	1
Condu	uctor Count:	1	

## Insulation

Material	Nominal Diameter	Nominal Wall Thickness	Min. Average Wall Thickness
PVC - Polyvinyl Chloride	0.11 in	0.019 in	0.015 in

## **Construction and Dimensions**

## Stranding



## Cabling



## **Electrical Characteristics**

## Conductor DCR

Individual Pair Nominal Shield DCR	Max. Conductor DCR	Nominal Outer Shield DCR
6.9 Ohm/1000ft	6.9 Ohm/1000ft	6.9 Ohm/km

## High Frequency (Nominal/Typical)

Nom. Insertion Loss 6.9 dB/100m

#### Voltage

UL Voltage Rating 300 V RMS

## **Temperature Range**

Non-UL Temp Rating:	105°C
UL Temp Rating:	105°C

## **Mechanical Characteristics**

Bulk Cable Weight:	15.7 lbs/1000ft
Min. Bend Radius/Minor Axis:	0.44 in

## **Standards**

UL Rating:	300V RMS, 105°C
UL AWM Style Compliance:	UL AWM Style 1569
CSA Rating:	300V, 105°C
CSA Type:	TRSR-64

## **Applicable Environmental and Other Programs**

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU (RoHS 2 amendment):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
CA Prop 65:	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LS0H, Toxicity Testing

UL Flammability:	VW-1
CSA Flammability:	FT1
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

lenum (Y/N):
--------------

## **Part Number**

### Variants

Item #	Color	Put-Up Type	Length	UPC
9989 0101000	Black	Reel	1,000 ft	612825267584
9989 0131000	Blue, Dark	Reel	1,000 ft	612825267591
9989 0011000	Brown	Reel	1,000 ft	612825267546
9989 0021000	Red	Reel	1,000 ft	612825267553
9989 0071000	Violet	Reel	1,000 ft	612825267560
9989 0091000	White	Reel	1,000 ft	612825267577

Footnote: P - STRIPE COLORS ON STOCK SOLID COLORS. STRIPING ADDER OF \$8.00/M= FOR 1 OR 2 STRIPES. 10,000' MINIMUM ORDER FOR COLOR COMBINATION. PUT-UP WILL BE SUBJECT TO TWO PIECES (+ OR -) 10% PER SPOOL, WITH A MINIMUM LENGTH OF 100'.

## **History**

15-2021	

© 2022 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.